DD10 Mini Disposable Dryer

Mini disposable inline desiccant dryer – DD10

Used at the point-of-use, this disposable, mini inline desiccant dryer removes all traces of water vapor, oil vapor and dirt. It is often used directly upstream of blow guns or spray guns as final protection for critical parts blow off and paint spraying. Install in either direction; it functions in both directions.

A 40 micron, porous bronze element removes fine dirt particles, an oil removing media removes oil vapor, and desiccant beads adsorb water vapor. The see-through housing shows desiccant color change from the original orange to a green color in the desiccant beads, which indicates that the dryer needs to be replaced.

Features

Refrigeration

Disposable

Desiccant

Regenerative

Desiccant

- · Polycarbonate material allows clear desiccant visibility
- Disposable
- Used for parts blow off
- Protection for paint guns
- Non-toxic desiccant standard
- 1/4" port (NPT)

Non-metalic material

is highly resistant to

Dirtv

Air

Wet

chemicals.

1.69

(42.9)



DD10-02

Operating information

Operating temperature:	
Maximum	
Flow capacity:	
Pressure rating (max.):	
Weight:	

32°F to 130°F (0°C to 54°C) 130°F (54°C) 15 scfm (7.1 dm³/s, ANR) 125 psig (8.6 bar) 2.8 oz (79.4 g)

Installation

The DD10 is equipped with a 1/4" NPT (F) and (M) ports and can be installed in either direction. When installing the filter/dryer hand tighten to a leak proof seal. Do not use any mechanical means to hold the filter/dryer and do not over torque the threads.

Operation

See through housing shows

4th Stage Removes Residual

Desiccant Dust

Clean

Air

Dry

color change when dryer

needs replacement.

3rd Stage Removes

Water Vapor

3.75 (95.3)

2nd Stage Removes

1st Stage Oil Vapors

Removes Dirt

- 1. The unique feature of the filter/dryer design allows you to visually see when it is time to install a new DD10 by observing the color change from the original orange color to a complete green color in the desiccant beads.
- 2. Do not attempt to clean the filter/dryer as the use of solvents, ketones, etc., will adversely affect the plastic housing.
- 3. Keep the hose free of snags. Extra tension on the filter/dryer assembly could break the unit at the connecting ports. To clear stuck hoses, grasp hose below the filter/dryer.

Dryers

